



erluna

air butterfly
origin
natural



air butterfly origin natural

orluna

		2700K										
		SPOT			SOFT				SPECIALITY			
LIGHT VALUES	Beam Width FWHM	Ultra 8°	Spot 10°	Narrow 14°	Medium 26°	Wide 42°	Flood 50°	Wash 58°	Crisp 36°	Elliptical 10x45°	Elliptical 20x40°	
		Initial Lumens	533	953	1021	1021	1021	1021	1021	1021	953	953
		Engine Lumens	223	357	379	871	859	802	836	861	266	290
		Luminaire Lumens	195	351	379	635	650	610	651	691	210	252
		Engine Lm/W	29	29	33	76	75	70	73	76	22	24
		Luminaire Cd	7065	9911	5797	2068	1172	852	731	1698	768	1414
POWER	Voltage	36V	36V	34V				36V				
	Drive Current	180mA	300mA	300mA				300mA				
	Circuit Power (typ)	7.8W	12.2W	11.4W				12.2W				

		3000K										
		SPOT			SOFT				SPECIALITY			
LIGHT VALUES	Beam Width FWHM	Ultra 8°	Spot 10°	Narrow 14°	Medium 26°	Wide 42°	Flood 50°	Wash 58°	Crisp 35°	Elliptical 10x45°	Elliptical 20x40°	
		Initial Lumens	637	984	1138	1138	1138	1138	1138	1138	935	935
		Engine Lumens	223	368	401	947	944	897	909	943	235	274
		Luminaire Lumens	215	359	401	685	715	686	727	762	198	251
		Engine Lm/W	29	30	35	83	83	79	80	83	19	22
		Luminaire Cd	8274	9755	6702	2271	1327	989	838	1954	744	1408
POWER	Voltage	36V	36V	34V				36V				
	Drive Current	180mA	300mA	300mA				300mA				
	Circuit Power (typ)	7.8W	12.2W	11.4W				12.2W				

Binning SDCM (Hot)	2
CRI (typ)(R9)	98 (99)
TM30 Rf Rg	Rf 97.7 Rg 100.4
Lifetime (TM21)	L90 B5 50,000hrs (inc driver)
Lifetime (Calculated)	L70 426,000hrs
Protocols	Mains Dim / DALI / 0-10V / Non-dim
Dim to Dark	0.1% Lux
Distance from LED	20m / 65' (series wiring)
Emergency	Emergency packs available

SPECIFICATION CODE

Engine type	Bezel	Colour Temp	Driver	Beam Width	Bezel Colour	Baffle Colour	Options
NL	AB	27	M	M	W	BB	54 K
		27 / 2700K 30 / 3000K 40 / 4000K	M / Mains Dim D / DALI 0 / 0-10v N / Non Dim X / No Driver	U / Ultra S / Spot N / Narrow M / Medium W / Wide F / Flood H / Wash C / Crisp L / Elliptical Linear O / Elliptical Oval	W / White RAL 9010 D / White RAL 9003 E / White RAL 9016 B / Black RAL 9005 C / Other RAL G / Polished Brass J / Antique Bronze K / Brushed Chrome L / Polished Chrome I / Polished Copper Z / Other Metallic	BB / Black 9005 WB / White 9010 DB / White 9003 EB / White 9016 CB / Other RAL MB / Polished Brass JB / Antique Bronze KB / BrushedChrome LB / PolishedChrome IB / Polished Copper ZB / Other Metallic	54 / IP54 J / Plaster-in plate H / Honeycomb N / Frosted Lens Z / LSZH Cable K / Click Connector

22/09/20