



duet origin natural



	2700K	
	SPECIALITY	
LIGHT VALUES	Double Wallwash Asymmetrical	
	Beam Width FWHM	
	Initial Lumens	1021
	Engine Lumens	727
	Luminaire Lumens	727
	Engine Lm/W	64
	Luminaire Cd	398
POWER	Voltage	34V
	Drive Current	300mA
	Circuit Power (typ)	11.4W

	3000K	
	SPECIALITY	
LIGHT VALUES	Double Wallwash Asymmetrical	
	Beam Width FWHM	
	Initial Lumens	1138
	Engine Lumens	846
	Luminaire Lumens	846
	Engine Lm/W	74
	Luminaire Cd	488
POWER	Voltage	34V
	Drive Current	300mA
	Circuit Power (typ)	11.4W

BINNING	SDCM (Hot)	2
	CRI (typ)(R9)	98 (99)
	TM30 Rf Rg	Rf 93.8 Rg 100.9
	Lifetime (TM21)	L90 B5 50,000hrs (inc driver)
	Lifetime (Calculated)	L70 426,000hrs
DRIVER	Protocols	Mains Dim / DALI / 0-10V / Non-dim
	Dim to Dark	0.1% Lux
	Distance from LED	20m / 65' (series wiring)
	Emergency	Emergency packs available

SPECIFICATION CODE

Engine type	Bezel	Colour Temp	Driver	Beam Width	Bezel Colour	Options
NL	DU	27	M	A	W	F 54 E
		27 / 2700K 30 / 3000K 40 / 4000K	M / Mains Dim D / DALI 0 / 0-10v N / Non Dim X / No Driver	A / Asymmetrical	W / White RAL 9010 D / White RAL 9003 E / White RAL 9016 B / Black RAL 9005 C / Other RAL	F / 60 min Fire Rated Plate 54 / IP54 65 / IP65 P / Sea & Spa IP65 *C / Constant Torsion J / Plaster-In Plate E / 3hr Emergency Z / LSZH Cable K / Click Connector

*NOTE: Fire Hood if used with constant torsion springs

